

A photograph of a clear asphalt road with a yellow center line, stretching into the distance through a dense forest of snow-covered evergreen trees. The sky is a clear, bright blue. The road is flanked by snow-covered shoulders, and a few cars are visible in the distance.

A Clear Road to Performance

LIQUIDOW™
Calcium Chloride

.....
The High-Value Prewetting Agent
for Rock Salt and Abrasives

Make Fast Work of Road Maintenance

To combat the snow and ice season, smart road-maintenance professionals think fast by prewetting rock salt and abrasives with LIQUIDOW™ Calcium Chloride to enhance the ice-melting process. Prewetted granular materials are proven to outperform their dry counterparts, speeding up the maintenance process and reducing the amount of granular materials used.

The low freezing point and 32% calcium chloride concentration of LIQUIDOW™ combine to boost the granular materials' effectiveness, achieving more efficient chemical usage. With LIQUIDOW™, road crews can melt snow and ice faster, and reduce road-maintenance costs.



Special Agent at Work

When rock salt is prewetted with LIQUIDOW™ Calcium Chloride, it provides:

- Fast ice-melting action
- Improved low-temperature performance
- Fewer losses from bounce and scatter
- High-quality road-maintenance service
- Overall reduced ice-melting cost

Prewetting abrasives, such as sand and cinders, with LIQUIDOW™ results in:

- Better imbedding of the material in packed snow and ice
- Improved traction
- Fewer losses from bounce and scatter





In Liquid Form

LIQUIDOW™ Calcium Chloride is an amazing liquid purified from a naturally occurring underground brine.

Road Tested and Approved

Recent independent studies support the effectiveness of using liquid calcium chloride to prewet rock salt.

Results of a study conducted in Ontario showed that prewetted rock salt outperformed dry salt in most test cases, reducing snow cover up to 40%. This research also showed that as a prewetting agent calcium chloride was “much more effective than magnesium chloride brine.” Calcium chloride outperformed up to 71% in terms of reduction of average snow cover. Calcium chloride brine was also more effective than salt brine.¹

In another study, the time required for road friction to increase to the traction level of wet pavement was measured after applications of both dry and prewetted rock salt. Dry rock salt was ineffective at 14°F (-10°C), but wet-pavement friction was recovered at this temperature with prewetted mixtures.²

¹Data collected by the Ontario Ministry of Transportation. Findings presented by Liping Fu, Rudolph Sooklall and Max S. Perchanok at the 2006 Transportation Research Board meeting. Reported in “Winter Strategies for 2006-2007,” Ruth W. Stidger, *Better Roads* magazine, June 2006

²Laboratory Melting Performance Comparison; Rock Salt With and Without Prewetting, Sixth International Symposium on Snow Removal and Ice Control Technology, June 7-9, 2004, Spokane, WA

An Extensive Value Package

With 32% calcium chloride concentration, LIQUIDOW™ is clearly a high-value agent for prewetting applications. As an added-value package, our customers rely on our consistent quality and supply, quick response, and leading technical service and support.

Contact a LIQUIDOW™ distributor today to see how this prewetting agent can get more value out of your rock salt and abrasives.

Quality Is Standard

LIQUIDOW™ Calcium Chloride meets or exceeds ASTM D98 and AASHTO M144 standard specifications for calcium chloride purity.

LIQUIDOW™
Calcium Chloride

For more information or to find an authorized distributor of
OxyChem's calcium chloride products, please call or visit our website.

(888) 293-2336

www.oxycalciumchloride.com

Important: The information presented herein, while not guaranteed, was prepared by technical personnel and is true and accurate to the best of our knowledge. **NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY OR OTHERWISE.** This information is not intended to be all-inclusive as to the manner and conditions of use, handling, storage, disposal and other factors that may involve other or additional legal, environmental, safety or performance considerations, and OxyChem assumes no liability whatsoever for the use of or reliance upon this information. While our technical personnel will be happy to respond to questions, safe handling and use of the product remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any Federal, State, local or foreign laws.



Occidental Chemical Corporation

A subsidiary of Occidental Petroleum Corporation