

INSTARMAC PERMANENT ROAD REPAIR®

APPLICATIONS

Instarmac Permanent Road Repair® is a Permanent Cold Lay Asphalt for first time permanent repairs in asphalt. It offers the benefits of an instant, first time permanent restoration, which when compacted, can be trafficked immediately.



easy to lay material is supplied. It should be noted if storage guidelines are not followed the material can appear stiff. By placing point load pressure on the bag, you will regain workability.

HEALTH, SAFETY AND ENVIRONMENTAL

Please ensure that appropriate PPE is used when preparing, mixing and applying products. Always wash your hands before consuming food and make sure that materials are kept safely out of reach of children and animals. Please dispose of packaging and waste responsibly and in accordance with local authority requirements. A full material datasheet relating to this product is available from Da-Lee.

QUALITY ASSURANCE

Our products are guaranteed against defective materials and manufacture, and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot however accept any liability arising from the application or use of our products because we have no direct or continuous control over where and how our products are used. All products are sold to our conditions of sale, copies of which can be obtained on request.

TECHNICAL DATA

PSV	65
Colour	Black
Coverage	Approx 1m ² at 12-15mm compacted, depending on the surface regularity of the restoration.

TECHNICAL

Instarmac Permanent Road Repair® includes fully graded, high PSV interlocking aggregate as well as specially formulated bitumen, containing polymers and flexibility. It also forms part of the Instarmac Manhole Repair System.

APPLICATION FOR A POTHOLE REPAIR

1. Ensure area is clean from debris
2. Seal the pothole edges and substrates using Instarmac SCJ
3. Fill patch with Permanent Road Repair
4. compact using jumping jack or vibrating plate

APPLICATION FOR FIRST TIME REPAIRS

1. Saw cut a 'picture frame' around the repair or restoration area
 2. Ensure the area is clear of debris
 3. Seal vertical edges and substrate with Instarmac SCJ
- Reinstatements requiring up to 100mm in depth can be achieved by using the layer-on-layer method.
4. Apply the product to a depth of approximately 75mm and compact to 50mm in order to achieve your first layer.
 5. Re-apply SCJ to vertical edges before a second layer of Instant Road Repair is applied
 6. Repeat step 4 to achieve the 100mm depth

STORAGE

Store inside above 5°C/41°F.

SHELF LIFE

Shelf life in correct conditions for sealed goods is 6 months. Delivered on shrink wrapped pallets.

HANDLING GUIDELINES

Instarmac Permanent Road Repair® is manufactured and delivered within as short a time as possible to ensure fresh,

Contact Us

Da-Lee Group, 350 Jones Road, Stoney Creek, ON L8E 5N2, Canada
Tel: 905 643 1135 Email: contact@daleegroup.com Website: daleegroup.com